

WORKBOAT SERIES

USWATERMAKER, INC.

Production Capacity (GPD)	500 to 2400 GPD
Raw Water Flow	2.3 to 5 GPM
Pre-filter	Commercial 5 & 25 Micron
Motor TEFC Close Coupled	1.5 to 5 HP
Phase	Single or Three Phase
Volts	115 or 230 (1.5 HP Single Phase) 12.8 or 6.4 Amps 230 (3 HP Single Phase) 13.2 Amps 208, 230 or 460 (Three Phase) 9, 8.6 or 4.3 Amps
Frame Dimensions	14.5" High x 26" Wide x 18.25" Deep
High Pressure Pump	CAT PUMPS® 3CP or 5CP, 316 Stainless Steel Pump
High Pressure Control	Adjustable Pressure Regulator and Safety Switch
Low Pressure Control	Low Pressure Safety Switch
Pressure Vessels	Composite with Anodized Aluminum End Plugs
Membranes	Seawater 2540 or 4040
Operating Pressures	800 PSI
Feed Pump	Composite Magnetic Drive or NAB Centrifugal
Feed Pressure	2 PSI Minimum
Raw Water Connection	¾" Hose Barb
Waste Water Connection	½" Hose Barb
Product Water Connection	½" Hose Barb
Fresh Water Flush	Automatic, ½" Hose Barb